

Rating @ 0.8 PF		Prime rating	Stand-by rating
Voltage * ¹	Freq.* ²	PT150* ³	PT165S* ⁴
400V	50 Hz	150.0 KVA	165.0 KVA

The above ratings represent the generating set capability guaranteed within + 3% at the reference conditions equivalent to those specified in ISO 8528/1, ISO 3046/1 and BS 5514/1

NOTES

1. The applicable voltage range is 380V to 415V for 50 Hz application and 380V to 480V for 60 Hz applications.
2. This generating set is of switchable speed of 1500rpm/1800rpm.
3. PT150 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Nothing that a 10% overload is available for 1 hour in every 12 hours operation.
4. PT165S is standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Nothing that no overload is permitted.

Engine Technical Data		
Model	Perkins 1006TAG2	
Cylinders	6; vertical in-line	
Aspiration	Turbocharged, air to air charge cooled	
Combustion	Direct injection	
Cooling System	Water cooled	
Displacement	5.99 L	
Oil consumption	0.2% of fuel consumption	
Lube oil capacity	19 L	
Coolant capacity	41.0 L	
Governor	Electronic	
Emissions regulations	Non-compliant	
Speed	1500 rpm	1800 rpm
Fuel Consumption PT150	37.3 L/H	---
Fuel Consumption PT165S	45.0 L/H	---
Radiation Cooling Air Flow	154 m ³ /min	---
Max Exhaust Gas Flow	29.1 m ³ /min	---

The above performance data are valid as per the following specs:

- * Diesel Fuel is according to BS2869 Class A2 or equivalent.
- * Lubricating oil is according to API CG4 (15W/40).
- * The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data		
Model	Leroy Somer LSA 44.2 M95	
Regulation	±0.5%	
International protection	IP23	
Insulation class	H	
Terminals	12	
Frequency	50 Hz	60 Hz
Coolant Air Flow	0.37 m ³ /s	---

Shipping Data			
Length	Width	Height	Weight
2500 mm	770 mm	1350 mm	1500 kg