

Rating @ 0.8 PF		Prime rating	Stand-by rating
Voltage * <sup>1</sup>	Freq.* <sup>2</sup>	PT200* <sup>3</sup>	PT220S* <sup>4</sup>
400V	50 Hz	200.0 KVA	223.0 KVA

The above ratings represent the generating set capability guaranteed within + 3% at the reference conditions equivalent to those specified in ISO 8528/1, ISO 3046/1 and BS 5514/1

#### NOTES

1. The applicable voltage range is 380V to 415V for 50 Hz application and 380V to 480V for 60 Hz applications.
2. This generating set is of switchable speed of 1500rpm/1800rpm.
3. PT200 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Nothing that a 10% overload is available for 1 hour in every 12 hours operation.
4. PT220S is standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Nothing that no overload is permitted.

Engine Technical Data		
<b>Model</b>	Perkins 1306C-E87TAG3	
<b>Cylinders</b>	6; vertical in-line	
<b>Aspiration</b>	Turbocharged & A/A charge-cooled	
<b>Combustion</b>	Direct injection	
<b>Cooling System</b>	Water cooled	
<b>Displacement</b>	8.7 L	
<b>Oil consumption</b>	0.1% of fuel consumption	
<b>Lube oil capacity</b>	28.3 L	
<b>Coolant capacity</b>	37.2 L	
<b>Governor</b>	Electronic	
<b>Emissions regulations</b>	EU stage2 & EPA tier2	
<b>Speed</b>	1500 rpm	1800 rpm
<b>Fuel Consumption PT200</b>	45.2 L/H	51.5 L/H
<b>Fuel Consumption PT220S</b>	49.1 L/H	56.9 L/H
<b>Radiation Cooling Air Flow</b>	375 m <sup>3</sup> /min	480 m <sup>3</sup> /min
<b>Max Exhaust Gas Flow</b>	36.5 m <sup>3</sup> /min	48.1 m <sup>3</sup> /min

The above performance data are valid as per the following specs:

- \* Diesel Fuel is according to BS2869 Class A2 or equivalent.
- \* Lubricating oil is according to API CH4 (15W/40).
- \* The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data		
<b>Model</b>	Leroy Somer LSA 46.2 M5	
<b>Regulation</b>	±0.5%	
<b>International protection</b>	IP23	
<b>Insulation class</b>	H	
<b>Terminals</b>	12	
<b>Frequency</b>	50 Hz	60 Hz
<b>Coolant Air Flow</b>	0.43 m <sup>3</sup> /s	0.51 m <sup>3</sup> /s

Shipping Data			
Length	Width	Height	Weight
2700 mm	990 mm	1750 mm	2000 kg